

# Orca 70

## Handheld Data Terminal



Salute to our classical Orca 50  
Newly upgraded

# 1. Advantages



## High Performance Computing Platform

Octa-core 64-bit Cortex-A55 processor (up to 2.0 GHz), plus a 200M RISC-V Co-processor make all kinds of massive data processing smoothly.



## Android 14.0

Android 14.0 OS, keeps optimizing and upgrading.



## Top Class Materials

Cast Aluminium + PC body, with tempered glass provide excellent rigidity + heat dissipation + electromagnetic shielding features. Soft material around the handle offers a comfortable grip.



## Industrial-grade Components

Industrial-grade and military-grade components ensure stable operation in harsh environments.



## Ultra Long Operating Time

Pistol style hot-swappable battery system makes backup battery more convenient to be restored, so that the operating time is unlimited.(Extra batteries are available.)



## High-end UHF RFID Engine

Equipped with self-developed UHF RFID module based on Impinj E710 chip, it is reputable in the industry for the outstanding reliability and stability and extremely strong multi-tag identification performance.



## Outstanding Industrial Design

The idea was inspired by orca, and each single detail has been well refined. The appearance is compact, elegant and balanced, which makes the product eye-catching and impressive.



## Excellent Mechanical Protection






Safety drop height 1.6m. IP64 protection grade.

## 2. Electrical Parameters

| Mechanical Parameters      |  |
|----------------------------|--|
| <b>Materials</b>           | Cast Aluminium + PC  |
| <b>Dimensions</b>          | 167mm*82mm*130mm<br>Grip 111mm*38mm*47mm                                   |
| <b>Weight</b>              | 615g ( Battery included )  |
| System Characteristics     |  |
| <b>Operating System</b>    | Android 14.0   |
| <b>CPU</b>                 | Octa-core 64-bit Cortex-A55 /up to 2.0 GHz<br>+ a 200M RISC-V Co-processor |
| <b>GPU</b>                 | G57 MC1  |
| <b>RAM+ROM</b>             | 4G+64G   |
| <b>LCD</b>                 | 5.0 inches/ 1280*720 / IPS / 180°view angle                                |
| <b>Touch Screen</b>        | 1.1mm thickness tempered glass/ 5- dot touch/ operable with gloves         |
| <b>Hotswapping Battery</b> | Pistol style hotswapping battery system                                    |
| <b>Power/Volume</b>        | 3 ALPS buttons/ Operating force 2.2N /<br>Operating life 1 million cycles  |
| <b>Scan Trigger</b>        | OMRON button / Operating force 1.27N/<br>Operating life 10 million cycles  |
| <b>Power</b>               | 6000mAh chargeable li-polymer battery                                      |
| <b>Card Slots</b>          | Nano SIM card slot*1 / TF card slot*1(Support<br>256G Micro T card)        |
| <b>USB Interface</b>       | USB 3.0 TYPE C (OTG supported)   |
| <b>Speaker Size</b>        | 28mm*9mm*3.8mm   |
| <b>Vibration</b>           | Button style / 10mm diameter   |

| Wireless Communications |                   |
|-------------------------|-------------------|
| <b>WIFI</b>             | 2.4G/5G Dual-Band |
| <b>Bluetooth</b>        | Bluetooth 5.0     |
| <b>LTE</b>              | Supported         |

| Application Environment   |                                |
|---------------------------|--------------------------------|
| <b>Operating Temp</b>     | -20°C~+60°C                    |
| <b>Storage Temp</b>       | -30°C~+70°C                    |
| <b>Work Humidity</b>      | 5%RH - 95%RH (non -condensing) |
| <b>Protection Grade</b>   | IP64                           |
| <b>Safety Drop Height</b> | 1.6m / 5.25ft                  |

| Data Collections  |  |   |   |
|---|--|---|---|
| 1D/2D Barcode   |  |   |   |
| 2D  | Datamatrix/QRCode/PDF417 US Planet/ UK Postal, etc.  |   |   |
|   |  |   |   |
| 1D  | UPC/EA Symbol SE955N/Code128/ Code39/Code93/Code11/Interleaved 2 of 5/ Discrete 2 of 5/Chinese 2 of 5/ Codabar/MSI/ RSS, etc.          |   |   |
|   |  |   |   |
| UHF RFID  |  |   |   |
| Sensitivity   | -88dBm   |   |   |
| Engine  | Rodinbell M-701 module based on Impinj E710 chip   |   |   |
| Protocol  | EPC Global UHF Class 1 Gen 2/ ISO 18000-6C   |   |   |
| Impinj Gen2X  | Supported  |   |   |
| Frequency   | 902~928MHz, 865~868MHz   |   |   |
| RF Output Power   | 0~33dBm  |   |   |
| Peak Inventory Speed  | >900tags/s   |   |   |
| UHF Antenna   | 4dBi circularly polarized antenna  |   |   |
| Read Distance   | >20m(Test with Impinj E41b inlay)  |   |   |
| Supported Regions   | US, Canada and other regions<br>Following U.S. FCC<br>Europe and other regions following ETSI EN 302 208<br>China<br>Korea<br>Malaysia |   |   |
|   |  |   |   |
| Camera  | 13 megapixels/ automatic focus/ flashlight   |   |   |
|   |  |   |   |
| Global positioning system   | GPS & GLONASS & Beidou   |   |   |
|   |  |   |   |
| Accessories   |  |   |   |
|  |   |  |  |
| Battery   | Desktop Charger<br><div>Optional </div>             | Charger & Data Cable  | Hanging Lace  |